व्यावसायिक परीक्षण रिपोर्ट(प्रारंभिक) COMMERCIAL TEST REPORT (INITIAL)

संख्या / No: Machine-293/1048 Month: August, 2019

Validity: 31.07.2024



STIHL MH 710 POWER WEEDER



भारत सरकार

Government of India कृषि एवं किसान कल्याण मंत्रालय

Ministry of Agriculture and Farmers Welfare कृषि, सहकारिता एवं किसान कल्याण विभाग

Department of Agriculture, Cooperation and Farmers Welfare दक्षिणी क्षेत्र कृषि मशीनरी प्रशिक्षण एवं परीक्षण संस्थान

Southern Region Farm Machinery Training and Testing Institute द्वैक्टर नगर, गार्लिक्ने-515 731, जिला: अनंतपूर (आं. प्र.)

Tractor Nagar, Garladinne-515 731, District: Anantapur (A.P.) [An ISO 9001:2015 CERTIFIED INSTITUTE]

Website: http://srfmtti.dacnet.nic.in/

E-mail: fmti-sr@nic.in Tele./FAX: 08551-286441

Machine- 293/1048

STIHL MH 710 POWER WEEDER

COMMERCIAL (ICT)

Manufacturer : M/s. Andreas STIHL Power Tools Ltd.,

Qingdao, China

(Designed by STIHL Tirol GmbH

Langkampfen, Austria)

Applicant : M/s. Andreas STIHL Pvt. Ltd.,

Gut No. 53/01, Pune - Nashik Highway, Kuruli, Pune - 410 501, Maharashtra, **India**

STIHL MH 710 POWER WEEDER

Report No.: Machine-293/1048 Month: August Year: 2019



Government of India

Ministry of Agriculture and Farmers Welfare Department of Agriculture, Cooperation and Farmers Welfare Southern Region Farm Machinery Training and Testing Institute Tractor Nagar, Garladinne-515 731, District: Anantapur (A.P.)

[An ISO 9001:2015 CERTIFIED INSTITUTE]

Telephone: 08551-286441 Fax: 08551-286441 Website: http://srfmtti.dacnet.nic.in/ E-mail: fmti-sr@nic.in

Machine- 293/1048

STIHL MH 710 POWER WEEDER

COMMERCIAL (ICT)

17. COMMENTS & RECOMMENDATIONS

17.1 Engine Performance:

- 17.1.1 The maximum power and rated power were observed as 5.2 kW under natural ambient condition against the declared value of 5.2 kW.
- 17.1.2 Specific fuel consumption of engine corresponding to maximum power was recorded as 248 g/kWh against the declared value of 355 g/kWh.
- 17.1.3 Max. Torque was observed as 17.5 Nm against the declared value of 15.6 Nm.
- 17.1.4 Back up torque of engine was observed as 5.42 %, against the declared value of 10 %. This should be looked into for corrective action
- 17.2 Max. Noise at operator's ear level was observed as 90 dB (A).
- 17.3 The amplitude of mechanical vibration on most of the assemblies of the Power Weeder was observed on higher side and to the maximum extent of 298 microns, Which is directly concerned with Operator's Health, Safety and Comfort. Besides, it also adversely affect the useful life of the components. In view of the above, this should be taken care for corrective action.
- 17.4 The hardness of rotary blades conforms to the requirement of IS 6690:1981 (Reaffirmed 2012).
- 17.5 The chemical composition of rotary blades conforms to the requirement of IS 6690:1981 (reaffirmed 2012).
- 17.6 Labeling plate provided should be as per the requirement of IS.

Machine-293/1048

STIHL MH 710 POWER WEEDER

COMMERCIAL (ICT)

17.7 Technical literature:

The instruction manual, work shop manual and parts catalogue of power weeder and engine were supplied with the test sample for reference during the test. It is however, recommended that same may be revised and bought out in Hindi & other regional languages as per IS 8132:1999 (Reaffirmed 2004) for the sake of user & technical personnel.

TESTING AUTHORITY:

B.N. DIXIT AGRICULTURAL ENGINEER	BI
Dr. P.P. RAO DIRECTOR	P-P. Rad

18. APPLICANT'S COMMENTS

Para No.	Our reference	Applicant's comments
(1)	(2)	(3)
18.1	17.1.4	Points noted on back up torque, we will take corrective action at the earliest.
18.2	17.3	Points noted on vibration, we will take corrective action at the earliest.
18.3	17.6	Points noted on labeling plate, we will take corrective action at the earliest.

ANANTAPUR, (A.P.)