

व्यावसायिक परीक्षण रिपोर्ट (प्रारंभिक)

COMMERCIAL TEST REPORT

संख्या / No: PT-139/1115

माह / Month: January, 2020

Validity: 31.12.2024

COMMERCIAL TEST (SECOND BATCH TEST)



KAVI DF 15L POWER TILLER



भारत सरकार

Government of India

कृषि एवं किसान कल्याण मंत्रालय

Ministry of Agriculture and Farmers Welfare

कृषि, सहकारिता एवं किसान कल्याण विभाग

Department of Agriculture, Cooperation and Farmers Welfare

दक्षिणी क्षेत्र कृषि मशीनरी प्रशिक्षण एवं परीक्षण संस्थान

Southern Region Farm Machinery Training and Testing Institute

ट्रैक्टर नगर, गार्लदिन्ने - 515 731, जिला: अनंतपुर (आं. प्र.)

Tractor Nagar, Garladinne- 515 731, District: Anantapur (A.P.)

[An ISO 9001:2015 CERTIFIED INSTITUTE]

Website: <http://srfmtti.dacnet.nic.in/>

E-mail: fmti-sr@nic.in

Tele./FAX: 08551-286441

PT- 139/1115	KAVI DF 15L POWER TILLER	COMMERCIAL (SECOND BATCH TEST)
-------------------------	---------------------------------	---

Manufacturer : M/s. Changzhou Lianfa Machinery Co. Ltd., 292, North Xintang Road, Changzhou, Jiangsu– 213 021, **China.**

Applicant : M/s. Kavi Agro Agency, 164, Kumaran Road, Sangiliyandapuram Main Road, Trichy– 620 001, Tamil Nadu, **India.**

Indigenous/ Imported : **Imported**

KAVI DF15L POWER TILLER

Report No.: PT-139/1115

Month: January

Year: 2020



Government of India
Ministry of Agriculture and Farmers Welfare
Department of Agriculture, Cooperation and Farmers Welfare
Southern Region Farm Machinery Training and Testing Institute
Tractor Nagar, Garladinne- 515 731, District: Anantapur (A.P.)
[An ISO 9001:2015 CERTIFIED INSTITUTE]



Telephone No. 08551-286441
Website: <http://srfmtti.dacnet.nic.in/>

Fax No.08551-286441
E-mail: fmti-sr@nic.in

PT-139/1115		KAVI DF 15L POWER TILLER		COMMERCIAL (SECOND BATCH TEST)
1	2		3	4
	-Maximum equivalent crankshaft torque, (Nm)	:	55.1	54.61
	-Back-up torque, (%)	:	7.83	5.92
	Maximum temperature, (°C):	:		
	-Engine oil	:	120	108
	-Coolant (water)	:	105	101
	-Exhaust gas	:	530	376
	-Air intake	:	45	45
	Lube oil consumption, (g/kWh)	:	0.52	0.68
19.2.2	Rotary shaft performance:			
	-Maximum power, (kW)	:	10.0	9.2
	-Specific fuel consumption corresponding to maximum power at rated engine speed, (g/kWh)	:	257	295
	-Maximum rotary shaft torque, (Nm)	:	502.7	477.4
	Maximum operating temperature of rotary transmission oil, (°C)	:	81	54
19.2.3	Drawbar performance:			
	Maximum drawbar power, (kW)	:	5.0	5.2
	Maximum drawbar pull, (KN)	:	3.7	3.7
	Maximum transmission oil temperature, (°C)	:	63	51
19.2.4	Parking Brake:			
	Maximum breaking device control force, (N)	:	254	271
	Efficacy of parking brake	:	Effective	Effective
19.2.5	Noise measurement:			
	Maximum noise at by-standard's position, dB(A)	:	81	83
	Maximum noise at operator's ear level, dB(A)	:	96	96
19.2.6	Air cleaner oil-pull-over test:			
	Maximum oil pull over (%)		0.22	0.16

PT-139/1115		KAVI DF 15L POWER TILLER		COMMERCIAL (SECOND BATCH TEST)
1	2		3	4
9.2.7	Mechanical vibration:			
	Maximum amplitude of vibration at, (micron):			
	-Gear shifting lever	: 162		160
	-Steering handle grip	: 191		190
	-Rotary shaft speed change lever	: 119		150
	-Steering clutch lever	: 241		320
	-Accelerator lever	: 185		220
9.2.8	Haulage test:			
	-Gross mass of trailer, (tones)	: 1.5		1.5
	-Av. traveled speed, (kmph)	: 15.06		16.63 to 17.30
	-Distance traveled per liter of fuel consumption, (km)	: 12.19		11.63 to 11.98
	-Av. fuel consumption, (cc/km/tonne)	: 54.69		55.65 to 57.32
9.3	Maintenance/service problems:	: None of the problems was observed in the previous sample.		None of the problems was observed in the present sample.
9.4	Adequacy of literature:	: Operation manual, Part catalogue and Workshop/service manual of Power Tiller and Engine		Operation manual cum Part catalogue of Power Tiller and Engine

TESTING AUTHORITY:

B.N. DIXIT AGRICULTURAL ENGINEER	
Dr. P.P. RAO DIRECTOR	

20. APPLICANT'S COMMENTS

Para No.	Our reference	Applicant's comments
20.1	18.17.3	As per your suggestion, we will inform to our manufacture to reduce the mechanical vibration of power tiller
20.2	18.17.4	As per your suggestion, we will inform to our manufacture to reduce the noise level of power tiller